

Rules Disclaimer 2019

The rules and/or regulations set forth herein are designed to provide for the orderly conduct of racing events and to establish minimum acceptable requirements for such events. These rules shall govern the condition of all events, and, by participating in these events, all participants are deemed to have complied with these rules. **NO EXPRESS OR IMPLIED WARRANTY OF SAFETY SHALL RESULT FROM PUBLICATION OF OR COMPLIANCE WITH THESE RULES AND/OR REGULATIONS.** They are intended as a guide for conduct of the sport and are in no way a guarantee against injury or death to participants, spectators, officials, or others. The series and/or track officials shall be empowered to permit minor deviation from any of the specifications herein or impose any further restrictions that in his/her opinion do not alter the minimum acceptable requirements. **NO EXPRESSED OR IMPLIED WARRANTY OF SAFETY SHALL RESULT FROM SUCH ALTERATION OF SPECIFICATIONS.**

Eligible Vehicles

1. Any three, four-cylinder, and six-cylinder front wheel drive car with a maximum wheelbase of 107.1" or less with the following exceptions:
2. **NO** Convertibles, **NO** Two Seat Coupes, **NO** Turbo or Supercharged Engines.
3. This is a true "Stock Car" class. We expect a stock engine for that make and model from the **throttle body** to the exhaust manifold, stock transmission, stock frame, stock steering, stock front & rear firewalls, stock dashboard, stock steering column, stock pedals, stock unaltered differential, no welded or locked differentials.

Preparation of Vehicle

1. Remove all insulation and upholstery from the interior and under the hood
 - a. Cars must retain original factory gauges.
2. Remove all the Airbags.
3. All holes in floor or firewall must be covered with securely mounted steel.
4. Sunroof opening must be sealed off with securely mounted steel.
5. Exterior mirrors **allowed on Black Top ONLY**. Factory interior mirror allowed.
6. Remove all glass except windshield.
 - a. If windshield is removed cars must have a minimum of three (3) 3/8" support braces.
 - b. Lexan or wire mesh 1" or smaller with .035 or larger wire **complete windshield opening side to side must be covered.**
7. Seat and Seatbelts
 - a. 5 point racing harness, including crotch belt required.
 - b. Shoulder belts need to be supported at shoulder level **lap belt mounts should swivel.**
 - c. Racing seats allowed, securely mounted to the roll cage. **Secure both the bottom and the back with oversize washers.**
 - d. All seats must have a headrest.
8. Battery
 - a. If relocated, must be secured by minimum 1/8" x 1" steel strap with minimum 3/8" hardware with large head washers.
 - b. No matter location, Battery must be secure and battery must be covered.
9. Gas Tank
 - a. Stock tank may remain in place if it is ahead of the rear axle.
 - b. If behind the rear axle it must be replaced with a fuel cell or boat tank (8 gallons or less) and mounted in the trunk.
 - c. Fuel cell or boat tank must be secured by minimum of four (4) 1/8" x 1" steel straps with minimum 3/8" hardware with large head washers. **NO** plumbers tape.
 - d. If fuel cell is used, trunk firewall must be sealed off.
 - e. If fuel line runs through the car, it must be in a sealed conduit.
 - f. Cars with fuel leaks will not be allowed to run.
10. Brakes
 - a. All cars must have functioning four- wheel brakes.
 - b. Cars not appearing to have adequate brakes will be black flagged.
11. Hood and Trunk
 - a. Hood may **NOT** be gutted. Trunk may be gutted since trunks/hatches are not required.
 - b. Hood must be on the stock, working hinges
 - c. Factory hood latch can be replaced with hood pins or seatbelts.
12. Bumpers
 - a. Bumper must be stock.
 - b. Bumpers should be chained or strapped to the frame.
 - c. Damaged bumpers may be replaced with another car bumper or may be fabricated out of a single tube no larger than 2½" in

- diameter no thicker than .095. Metal bumpers should be capped to fenders.
- d. NO angle iron, NO channel iron, NO additional bracing, NO trailer hitches.
- e. **Inspector has discretion and final say on all "repairs".**

13. Doors

- a. Doors must be welded or chained shut.
- b. Driver's side door bars are required – see Roll Cage and Bars later in the rules.
- c. If you do not have 3 door bars, driver's door must be plated – see Roll Cage and Bars later in the rules.
- d. Rub rails allowed IF and only if they are securely fastened, have no sharp edges, have no chance of

hooking another car, stick out no more than ¼".

14. Tires, Wheels and Lug nuts

- a. Stock wheels for make and model of car.
- b. Right front wheel may be a stock offset, stock width - safety wheel. **Aero Series 44 is the only dimensionally correct wheel**
- c. Both front wheels must have oversized lug nuts
- d. Maximum wheel width 6"
- e. Front tires must be exact equal markings for size and profile. Rear tire stagger is allowed, even different rim sizes.

- f. Passenger car tires only **No Snow Tires** – No recaps, no made for racing "cheater tires".

g. Stick shift cars Maximum 60 series tire (65, 70 75's okay). Automatic transmission cars may use 55 or 50 series tires.

h. NO SNOW TIRES!

- i. Maximum section width of any tire is 225.

j. Tread Wear. All tires must have a UTQG rating of 260 or higher. **If there's no treadwear clearly marked you can't run it.**

15. Exhaust

- a. **NO open exhaust.** Every car MUST have a stock muffler or catalytic converter.
- b. Exhaust MUST exit behind the driver.
- c. Exhaust cannot point at the gas tank.
- d. Maximum exhaust size is 2" I.D.
- e. Strap on your exhaust good – you can expect a black flag if it falls off.

16. Radiator and Protection

- a. Any radiator in the stock location is allowed.
- b. A radiator protection bar constructed of 1" tubing no thicker than 1/8" is allowed. May not tie into strut towers.

c. A maximum of 6' total of tubing may be used for the radiator protection bar(s), uprights and braces and any bracing.

17. Suspension – Stock spring, struts, shocks.

- a. Stock springs may be altered. No racing springs.
- b. Stacking of bump rubbers allowed on right rear only.
- c. **Cars should sit level. Cars that appear overly set up will be given a penalty based on looks alone.**

Safety Requirements

1. Snell **2005** (or newer) helmet.
2. Full racing firesuit recommended (either one piece or shirt and pants). Long sleeves and long pants mandatory.
3. Gloves required – racing gloves strongly recommended.
4. Racing shoes or boots strongly recommended.
5. Neck collar or other style head and neck restraint required – neck collar is minimum.

Roll Cage and Bars

1. Roll Cage

- a. Tubing size is 1½" x .095 thickness is highly recommended. Square tubing is ok.
- b. Single hoop roll bar with a minimum 2 angled down bars must be welded or bolted with sandwich plates (4" x 4" x 1/8") to the car.
- c. Hoop must be full height and width of car.
- d. **The minimum required 2** Down bars must connect at a point at least 2/3rds of the way up the hoop.
- e. Hoops should be bent in a bender (not kinked) or miter cut and gusseted.

2. Door Bars – Tracks Longer than ¼ Mile

- a. A minimum of 3 door bars on the driver's side going forward from your main roll bar hoop to a vertical bar (forward post) at least dashboard height. This bar may be welded on the bottom to the rocker panel and on the top to the windshield pillar.

- b. If the forward post is not welded solid between the rocker and windshield pillar then it must be connected side to side by a dashboard bar (factory bar acceptable).
- c. The forward post may continue upward and be part of a conventional 4-point roll cage.
- 3. Door Bars – Tracks ¼ Mile The 3 door bars previously outlined are recommended.
 - a. If you are not using 3 door bars, a minimum of one bar welded to the main hoop (armpit height with driver seated) must go forward to at least the front edge of the door **AND**
 - b. A 5-foot long steel plate 1/8" thick by a minimum of 6" wide must be welded or bolted to the side of the door at bumper height. Two (2) plates are recommended starting at the rocker panel and going 12" up the door.
- 4. Rear bars may connect to the rear strut towers. Rear strut towers may be connected side to side.

Not Allowed

- 1. **NO radio communication allowed other than raceceiver communications from MCTS staff.**
- 2. NO cell phones.
- 3. NO bracing anywhere besides driver's compartment.
- 4. NO Great Stuff (or other expandable foam) allowed in fenders, quarters, etc.
- 5. Drain all anti-freeze – WATER ONLY in radiator. (Except New Year's Day)
- 6. NO trailer hitches.
- 7. NO ballast. Lead or other.

Additional Criteria

- 1. Cars must have legible numbers on both doors and roof.
- 2. Driver's name must be clearly lettered on both sides of the vehicle on the rear-most part of the quarter panel – higher than the bumper in letters at least 6" high.
- 3. No obscene, profane or distasteful slogans or markings allowed.
- 4. Camber is allowable to a maximum of 1 inch measured as the difference from the top of the rim to the bottom of the rim from a carpenter's square. Cutting/Welding/Slotting is allowed to obtain Camber
- 5. The confiscation (Car Claim) rule will be in effect at all MCTS events. **Cars may or may not be auctioned off on ebay.**
- 6. Raceceivers Mandatory

PROCEDURES

Entry Fee: Must be received one week prior to event to qualify for the pre-registration deadline

Line up: All pre-registered cars will be included in a random drawing to determine the starting lineup. Non-preregistered cars will be lined up behind the pre-registered grid in the order they pass tech. Cars that have not successfully passed tech 1 hour before the scheduled start time lose their starting position.

Scoring: Transponder scoring is used at MCTS events. Will be rented (for \$10) at the event. Non pre-registered cars receive rental units on a first come, first served basis.

Car Claim: The MCTS can keep the top 2 finishing cars. If the first or second place finisher refuses the car claim, they are disqualified and suspended from MCTS competition. All finishing positions move up.

Penalties: Cars not passing pre-race tech will be assessed any number of penalty laps at the start of the race.

Disabled Cars: Cars that become immobile and warrant a red flag will be left on the track as obstacles